

CLAIMS

What is claimed is:

1. A computer implemented method for calculating an importance rank for N linked nodes of a linked database, the method comprising the steps of:
 - (a) selecting an initial N -dimensional vector P_0 ;
 - (b) computing an approximation P_n to a steady-state probability P_∞ in accordance with the equation $P_n = A^n P_0$, where A is an $N \times N$ transition probability matrix having elements $A[i][j]$ representing a probability of moving from node i to node j ; and
 - (c) determining a rank $r[k]$ for a node k from a k^{th} component of P_n .
2. The method of claim 1 wherein the matrix A is chosen so that an importance rank of a node is calculated, in part, from a weighted sum of importance ranks of backlink nodes of the node.
3. The method of claim 2 wherein the importance ranks of each of the backlink nodes is weighted in dependence upon the total number of links in the backlink node.
4. The method of claim 1 wherein the matrix A is chosen so that an importance rank of a node is calculated, in part, from a constant α representing the probability that a surfer will randomly jump to the node.
5. The method of claim 1 wherein the matrix A is chosen so that an importance rank of a node is calculated, in part,

from a measure of distances between the node and backlink nodes of the node.

6. The method of claim 1 wherein the initial N-dimensional vector p_0 is selected to represent a uniform probability distribution.

7. The method of claim 1 wherein the initial N-dimensional vector p_0 is selected to represent a non-uniform probability distribution, wherein a predetermined set of nodes is given a relatively large initial probability.

8. A computer implemented method for assigning a rank to N nodes of a linked database, the method comprising calculating, for a node, a weighted sum of ranks of backlink nodes to the node, wherein each of the backlink nodes is weighted in dependence upon the total number of links in the backlink node.

Add A16